





用于供热、通风及空调系统的控制阀





















- 典型可调比 1 : 50 （并非所有阀都能达到）
- 泄漏率按照DIN EN 1349 • 金属密封：泄漏等级IV；软密封：泄漏等级VI

选择标准 · 表1

| 控制阀用于... | SAMSON产品包括以下控制阀 | | |
|----------|---|---|--|
| 过程工厂 | • | • | |
| 工业能源转换系统 | • | • | |
| 导热油 | | • | |
| 供热、通风及空调 | • | | |
| 区域供热 | • | | |
| | 尺寸可达 DN 50 (3323) DN 100 (3321) | 公称通径达 DN 80 | |
| | PN 10 至 PN 40 | PN 16 至 PN 25 | |
| | -10 至 + 300°C | -10 至 + 350 °C* | |
| | 不含有色金属 | 不含有色金属 | |
| | | *按要求，扩展的温度范围 可降至-70 °C。 | |
| |  V2001-E3/3321-E3 参见 T 8111 ZH |  V2001-P/3531-P 导热油 参见 T 8131 ZH | |
| |  V2001-IP/3323-IP 参见 T 8113 ZH |  V2001-E1/3535-E1 导热油 参见T 8135 ZH | |

注意:

用于瞬时供热系统中的生活热水及加热应用中的带控制器的电动执行器及阀, 参见产品信息表T 5700 ZH。

| | | | | |
|---|---|---|---|---|
| | • | | | |
| | • | • | • | |
| | • | | | |
| | • | • | • | • |
| | • | • | • | • |
| | 公称通径达DN 150 | 公称通径达 DN 50 | 公称通径达 DN 250 | 公称通径达 DN 250 |
| | PN 16 至 PN 40 | PN 25 | PN 16 至 PN 40 | PN 16 至 PN 40 |
| | -196 至 + 450 °C | -15 至 200 °C | -10 至 220 °C | 150 °C |
| | 无有色金属 | | | |
| | | | | 带附加电动执行器的阀 |
| |  |  |  |  |
|  3241/3274 型 参见T 5874 ZH  3244/3374 型 参见T 5870 ZH  3241-1 型带电磁阀 3701 型, 按要求可提供 |  3222/5825型, 参见T 5866 ZH  3222/5857 型, 参见T 5866 ZH  3226/5824型, 参见T 5863 ZH  3226/5857 型, 参见T 5863 ZH |  3213/5825 型 参见T 5868 ZH 及T 5869 ZH  3214/3274型 参见T 5868 ZH、 T5868-1ZH 和 T 5869 ZH  3260/5857 型 参见T 5861 ZH |  3267/5824 型 参见 T 5894  3260/3374型, 参见T 5861 ZH  42-36E型, 参见 T 3018 ZH  2488/5825 型 参见 T 3135 ZH  2487/5824 型 参见T 3135 ZH  42-37E型, 带3274-2 参见T 3018 ZH  2488/5857型 参见T 3135 ZH | |

规格数据可能由于技术进步而改变



萨姆森控制设备(中国)有限公司
北京经济技术开发区永昌南路11号 (100176)
电话: 010-67803011 传真: 010-67803193
E-mail: info@samsonchina.com
<http://www.samsonchina.com>

南京维修服务中心
江苏省南京市中山东路288号新世纪广场3506室 (210002)
电话: 025-84676696/98 传真: 025-84676697

上海分公司
上海市徐汇区零陵路899号
飞洲国际广场25楼J+K+L室 (200030)
电话: 021-54591580/81 传真: 021-54253866

广州分公司
广州市黄埔大道西33号三新大厦21楼E室 (510620)
电话: 020-38202422/23 传真: 020-38202416

成都分公司
成都天府大道南延线成都高新区
高新孵化园1号楼B-8-06 (610041)
电话: 028-85336626/27/28/29 传真: 028-85336630

沈阳分公司
沈阳市和平区和平北大街69号总统大厦C座1308室 (110003)
电话: 024-22814300 传真: 024-22814355

T 5800 ZH