


The Right Mix

Type 3260 Three-way Valve



- Available as a mixing or diverting valve
- Versions suitable for water and oil
- Valve sizes DN 15 to 300
- Nominal pressure PN 16
- Maximum medium temperature 150 °C



Possible combinations

Nominal size DN	15	20	25	32	40	50	65	80	100	125	150	200	250	300
K _{VS} coefficients	1 to 4	6.3	10	16	25	40	60	80	160	250	Max. 320	630	800	1200
Possible combinations ²⁾														
With electric actuator with digital positioner or using a three-stepping point signal (optionally with limit contacts and/or resistance transmitter depending on the version)														
Without fail-safe action	■	■	■	■	■	■	■	■	■	■	■	■	■	■
With fail-safe action	■	■	■	■	■	■	■	■	■	■	■			
With electric actuator with process controller for heating and cooling applications														
Without fail-safe action	■	■	■	■	■	■								
With fail-safe action	■	■	■	■	■	■								
With pneumatic actuator														
	■ ¹⁾	■ ¹⁾	■ ¹⁾	■ ¹⁾	■ ¹⁾	■ ¹⁾	■ ¹⁾	■ ¹⁾	■ ¹⁾	■ ¹⁾	■ ¹⁾	■	■	■

¹⁾ Suitable for integral positioner attachment

²⁾ Refer to Data Sheet T 5861 EN for more details

